FCom Tuning Fork Crystal

Series FCT-6M

SMD 32.768 kHz Crystal 6.9×1.4 mm

Feature

- Ultra small size 6.9×1.4×1.3 mm
- High reliability environmental performance
- High frequency stability and high precision

Application

- Consumer products
- Small mobile telecommunicationgs devices

ELECTRICAL SPECIFICATIONS

Parameters	Symbol	Min.	Typ.	Max.	Units	Notes	
Nominal Frequency	F	32.768			kHz		Test condition Ambient temperature: 25 ± 5°C Relative humidity: 40% ~ 70%
Frequency Tolerance (at 25°C)	FT	± 5, ± 10, ± 20			ppm	@-20~70°C	
		± 5, ± 10, ± 20			ppm	@-40~90°C	
Operating Temperature	Topr	-40	25	90	°C		
Load Capacitance	CL	6, 7, 9, 12.5 or specify			pF		
Drive Level	DL	-	-	1.0	uW		
Equivalent Series Resistance	ESR	-	-	65	Kohm		
Shunt Capacitance	C0	0.8			pF		
Temperature Coefficient	-	-0.035+0.01			ppm/T²		
Insulation Resistance	-	500	-	-	Mohm	DC100V±15V	
Aging	-	± 3			ppm	1st Year	

Note : The table shows common spec. if you have special spec. requirement , please feel free to contact our salesperson.

DIMENSION(mm)



Electrode Arrangement