

Complete P/N / Model	Series	Package	Center freq. (MHz)	Bandwidth (MHz)	Insertion loss (dB)	Stopband attn. (dB)	Mount	Technical file
FSF1109-707M-17M-2-30	FSF1109	CSP1109	707.0	17.0	2.0	30.0	SMD	Request PDF
FSF1109-742M5-27M-2.5-50	FSF1109	CSP1109	742.5	27.0	2.5	50.0	SMD	Request PDF
FSF1411-780M5-45M-1.6-40	FSF1411	CSP1411	780.5	45.0	1.6	40.0	SMD	Request PDF
FSF1411-782M-12M-1.6-40	FSF1411	CSP1411	782.0	12.0	1.6	40.0	SMD	Request PDF
FSF1109-836M-25M-2-40	FSF1109	CSP1109	836.0	25.0	2.0	40.0	SMD	Request PDF
FSF1411-836M-25M-2-40	FSF1411	CSP1411	836.0	25.0	2.0	40.0	SMD	Request PDF
FSF1411-847M-30M-1.6-40	FSF1411	CSP1411	847.0	30.0	1.6	40.0	SMD	Request PDF
FSF1109-876M5-35M-2-40	FSF1109	CSP1109	876.5	35.0	2.0	40.0	SMD	Request PDF
FSF1109-881M5-25M-1.5-40	FSF1109	CSP1109	881.5	25.0	1.5	40.0	SMD	Request PDF
FSF1411-881M5-25M-2.3-30	FSF1411	CSP1411	881.5	25.0	2.3	30.0	SMD	Request PDF
FSF1109-897M5-30M-2.5-40	FSF1109	CSP1109	897.5	30.0	2.5	40.0	SMD	Request PDF
FSF1109-897M5-35M-2-40	FSF1109	CSP1109	897.5	35.0	2.0	40.0	SMD	Request PDF
FSF1411-897M5-30M-2.5-40	FSF1411	CSP1411	897.5	30.0	2.5	40.0	SMD	Request PDF
FSF1411-897M5-35M-2-40	FSF1411	CSP1411	897.5	35.0	2.0	40.0	SMD	Request PDF
FSF1411-911M5-27M-1.6-40	FSF1411	CSP1411	911.5	27.0	1.6	40.0	SMD	Request PDF
FSF1109-915M-26M-1.5-50	FSF1109	CSP1109	915.0	26.0	1.5	50.0	SMD	Request PDF

Selection guidance: Please refer to the model datasheet for detailed specifications, test conditions and matching requirements. Contact FCom for assistance with product selection.

Values: Please contact FCom to confirm parameter definitions, typical or limit values, and test conditions for the listed specifications.

Bandwidth: The attenuation level used to define bandwidth is not specified in this catalog. Please refer to the model datasheet for the applicable definition.

Stopband: Please refer to the model datasheet for the applicable frequency intervals, attenuation reference and test conditions.

Complete P/N / Model	Series	Package	Center freq. (MHz)	Bandwidth (MHz)	Insertion loss (dB)	Stopband attn. (dB)	Mount	Technical file
FSF1411-915M-26M-1.5-50	FSF1411	CSP1411	915.0	26.0	1.5	50.0	SMD	Request PDF
FSF1109-942M5-35M-2.2-40	FSF1109	CSP1109	942.5	35.0	2.2	40.0	SMD	Request PDF
FSF1411-942M5-35M-2.2-40	FSF1411	CSP1411	942.5	35.0	2.2	40.0	SMD	Request PDF
FSF1109-1176M45-20M-1.4-40	FSF1109	CSP1109	1176.45	20.0	1.4	40.0	SMD	Request PDF
FSF1411-1176M45-20M-1.4-40	FSF1411	CSP1411	1176.45	20.0	1.4	40.0	SMD	Request PDF
FSF1109-1197M-62M4-1.3-20	FSF1109	CSP1109	1197.0	62.4	1.3	20.0	SMD	Request PDF
FSF1411-1202M-72M-2.4-30	FSF1411	CSP1411	1202.0	72.0	2.4	30.0	SMD	Request PDF
FSF1109-1268M52-20M46-1.7-40	FSF1109	CSP1109	1268.52	20.46	1.7	40.0	SMD	Request PDF
FSF1411-1561M89-21M-3.3-40	FSF1411	CSP1411	1561.089	21.0	3.3	40.0	SMD	Request PDF
FSF1411-1568M-18M32-1.6-40	FSF1411	CSP1411	1568.0	18.32	1.6	40.0	SMD	Request PDF
FSF1411-1573M-66M-2.8-30	FSF1411	CSP1411	1573.0	66.0	2.8	30.0	SMD	Request PDF
FSF1411-1575M42-2M4-1.1-40	FSF1411	CSP1411	1575.42	2.4	1.1	40.0	SMD	Request PDF
FSF1109-1582M4-46M-0.9-40	FSF1109	CSP1109	1582.4	46.0	0.9	40.0	SMD	Request PDF
FSF1109-1582M4-46M-1.8-40	FSF1109	CSP1109	1582.4	46.0	1.8	40.0	SMD	Request PDF
FSF1411-1582M4-46M-1.8-40	FSF1411	CSP1411	1582.4	46.0	1.8	40.0	SMD	Request PDF
FSF1411-1600M-40M-1.9-40	FSF1411	CSP1411	1600.0	40.0	1.9	40.0	SMD	Request PDF

Selection guidance: Please refer to the model datasheet for detailed specifications, test conditions and matching requirements. Contact FCom for assistance with product selection.

Values: Please contact FCom to confirm parameter definitions, typical or limit values, and test conditions for the listed specifications.

Bandwidth: The attenuation level used to define bandwidth is not specified in this catalog. Please refer to the model datasheet for the applicable definition.

Stopband: Please refer to the model datasheet for the applicable frequency intervals, attenuation reference and test conditions.

Ordering-code confirmation: FSF1411-1561M89-21M-3.3-40 is listed at 1561.089 MHz. Please contact FCom to confirm the ordering code and center frequency before ordering.

Complete P/N / Model	Series	Package	Center freq. (MHz)	Bandwidth (MHz)	Insertion loss (dB)	Stopband attn. (dB)	Mount	Technical file
FSF1411-1603M-12M-2.3-40	FSF1411	CSP1411	1603.0	12.0	2.3	40.0	SMD	Request PDF
FSF1411-1637M-2M-2-40	FSF1411	CSP1411	1637.0	2.0	2.0	40.0	SMD	Request PDF
FSF1109-1745M5-70M-1.8-30	FSF1109	CSP1109	1745.5	70.0	1.8	30.0	SMD	Request PDF
FSF1411-1745M5-70M-1.8-30	FSF1411	CSP1411	1745.5	70.0	1.8	30.0	SMD	Request PDF
FSF1109-1747M5-75M-1.3-30	FSF1109	CSP1109	1747.5	75.0	1.3	30.0	SMD	Request PDF
FSF1109-1747M5-75M-2.1-30	FSF1109	CSP1109	1747.5	75.0	2.1	30.0	SMD	Request PDF
FSF1411-1800M-40M-2-40	FSF1411	CSP1411	1800.0	40.0	2.0	40.0	SMD	Request PDF
FSF1109-1842M5-65M-2-40	FSF1109	CSP1109	1842.5	65.0	2.0	40.0	SMD	Request PDF
FSF1109-1842M5-75M-1.5-30	FSF1109	CSP1109	1842.5	75.0	1.5	30.0	SMD	Request PDF
FSF1109-1842M5-75M-2.5-40	FSF1109	CSP1109	1842.5	75.0	2.5	40.0	SMD	Request PDF
FSF1109-1880M-60M-2.2-30	FSF1109	CSP1109	1880.0	60.0	2.2	30.0	SMD	Request PDF
FSF1411-1880M-60M-2.2-30	FSF1411	CSP1411	1880.0	60.0	2.2	30.0	SMD	Request PDF
FSF1109-1900M-40M-1.7-30	FSF1109	CSP1109	1900.0	40.0	1.7	30.0	SMD	Request PDF
FSF1109-1950M-60M-1.6-30	FSF1109	CSP1109	1950.0	60.0	1.6	30.0	SMD	Request PDF
FSF1109-2140M-60M-1.8-40	FSF1109	CSP1109	2140.0	60.0	1.8	40.0	SMD	Request PDF
FSF1109-2155M-90M-2.6-30	FSF1109	CSP1109	2155.0	90.0	2.6	30.0	SMD	Request PDF

Selection guidance: Please refer to the model datasheet for detailed specifications, test conditions and matching requirements. Contact FCom for assistance with product selection.

Values: Please contact FCom to confirm parameter definitions, typical or limit values, and test conditions for the listed specifications.

Bandwidth: The attenuation level used to define bandwidth is not specified in this catalog. Please refer to the model datasheet for the applicable definition.

Stopband: Please refer to the model datasheet for the applicable frequency intervals, attenuation reference and test conditions.

Complete P/N / Model	Series	Package	Center freq. (MHz)	Bandwidth (MHz)	Insertion loss (dB)	Stopband attn. (dB)	Mount	Technical file
FSF1109-2350M-100M-2.3-30	FSF1109	CSP1109	2350.0	100.0	2.3	30.0	SMD	Request PDF
FSF1109-2437M-69M-1.1-30	FSF1109	CSP1109	2437.0	69.0	1.1	30.0	SMD	Request PDF
FSF1109-2442M-79M-1.2-40	FSF1109	CSP1109	2442.0	79.0	1.2	40.0	SMD	Request PDF
FSF1411-2442M-79M-1.3-40	FSF1411	CSP1411	2442.0	79.0	1.3	40.0	SMD	Request PDF
FSF1411-2442M-79M-2-40	FSF1411	CSP1411	2442.0	79.0	2.0	40.0	SMD	Request PDF
FSF1109-2492M-8M-6.5-30	FSF1109	CSP1109	2492.0	8.0	6.5	30.0	SMD	Request PDF
FSF1109-2535M-70M-2-30	FSF1109	CSP1109	2535.0	70.0	2.0	30.0	SMD	Request PDF
FSF1109-2593M-194M-2.1-40	FSF1109	CSP1109	2593.0	194.0	2.1	40.0	SMD	Request PDF
FSF1109-2593M-194M-2.2-40	FSF1109	CSP1109	2593.0	194.0	2.2	40.0	SMD	Request PDF
FSF1411-2593M-194M-2.2-40	FSF1411	CSP1411	2593.0	194.0	2.2	40.0	SMD	Request PDF
FSF1109-2595M-120M-1.6-30	FSF1109	CSP1109	2595.0	120.0	1.6	30.0	SMD	Request PDF
FSF1109-2595M-120M-2.5-30	FSF1109	CSP1109	2595.0	120.0	2.5	30.0	SMD	Request PDF
FSF1411-2595M-160M-1.5-40	FSF1411	CSP1411	2595.0	160.0	1.5	40.0	SMD	Request PDF
FSF1411-2595M-160M-2.5-40	FSF1411	CSP1411	2595.0	160.0	2.5	40.0	SMD	Request PDF
FSF1109-2655M-70M-2-30	FSF1109	CSP1109	2655.0	70.0	2.0	30.0	SMD	Request PDF
FSF1411-3500M-200M-2-40	FSF1411	CSP1411	3500.0	200.0	2.0	40.0	SMD	Request PDF

Selection guidance: Please refer to the model datasheet for detailed specifications, test conditions and matching requirements. Contact FCom for assistance with product selection.

Values: Please contact FCom to confirm parameter definitions, typical or limit values, and test conditions for the listed specifications.

Bandwidth: The attenuation level used to define bandwidth is not specified in this catalog. Please refer to the model datasheet for the applicable definition.

Stopband: Please refer to the model datasheet for the applicable frequency intervals, attenuation reference and test conditions.